

Product **connecting cable, overmoulded, F&B, stainless steel,PVC grey**
 Area **M12-A Series 763 FOOD & BEVERAGE**
 Article number **77 3730 3729 20908-0200**

Illustration	Scale drawing	Contact Arrangement																		
		<table border="1" style="margin-left: auto; margin-right: auto;"> <thead> <tr> <th>geschirmt/ shielded</th> <th>nicht geschirmt/ not shielded</th> </tr> </thead> <tbody> <tr> <td>1 weiß/white</td> <td>1 weiß/white</td> </tr> <tr> <td>2 braun/brown</td> <td>2 braun/brown</td> </tr> <tr> <td>3 grün/green</td> <td>3 grün/green</td> </tr> <tr> <td>4 gelb/yellow</td> <td>4 gelb/yellow</td> </tr> <tr> <td>5 grau/grey</td> <td>5 grau/grey</td> </tr> <tr> <td>6 rosa/pink</td> <td>6 rosa/pink</td> </tr> <tr> <td>7 blau/blue</td> <td>7 blau/blue</td> </tr> <tr> <td>8 rot/red</td> <td>8 Schirm/shield</td> </tr> </tbody> </table> <p style="text-align: center;">Gehäuse-Schirm/ Housing-shield</p>	geschirmt/ shielded	nicht geschirmt/ not shielded	1 weiß/white	1 weiß/white	2 braun/brown	2 braun/brown	3 grün/green	3 grün/green	4 gelb/yellow	4 gelb/yellow	5 grau/grey	5 grau/grey	6 rosa/pink	6 rosa/pink	7 blau/blue	7 blau/blue	8 rot/red	8 Schirm/shield
geschirmt/ shielded	nicht geschirmt/ not shielded																			
1 weiß/white	1 weiß/white																			
2 braun/brown	2 braun/brown																			
3 grün/green	3 grün/green																			
4 gelb/yellow	4 gelb/yellow																			
5 grau/grey	5 grau/grey																			
6 rosa/pink	6 rosa/pink																			
7 blau/blue	7 blau/blue																			
8 rot/red	8 Schirm/shield																			

Technical data

<h3 style="color: #0070C0;">General features</h3> <table border="0"> <tr> <td>Connector Design</td> <td>Cable Connector</td> </tr> <tr> <td>Connector locking system</td> <td>screw</td> </tr> <tr> <td>Termination</td> <td>crimp, overmoulded on cable</td> </tr> <tr> <td>Wire gauge (mm)</td> <td>0,25</td> </tr> <tr> <td>Wire gauge (AWG)</td> <td>24</td> </tr> <tr> <td>Upper temperature</td> <td>105 °C</td> </tr> <tr> <td>Lower temperature</td> <td>-40 °C</td> </tr> </table> <h3 style="color: #0070C0;">Cable data</h3> <table border="0"> <tr> <td>material housing</td> <td>PVC</td> </tr> <tr> <td>Insulation single lead</td> <td>PVC</td> </tr> <tr> <td>Single lead structure</td> <td>32 x 0,1</td> </tr> <tr> <td>Cable sheath Ø</td> <td>6</td> </tr> <tr> <td>Conductor resistance</td> <td><79 Ω/Km (20°C)</td> </tr> <tr> <td>Temperature range cable movable °C from</td> <td>-5</td> </tr> <tr> <td>Temperature range cable movable °C to</td> <td>105</td> </tr> <tr> <td>Temperature range cable fixed °C from</td> <td>-40</td> </tr> <tr> <td>Temperature range cable fixed °C to</td> <td>105</td> </tr> <tr> <td>Bending radius cable fixed</td> <td>min. 5 x D</td> </tr> <tr> <td>Bending radius cable movable</td> <td>min. 10 x D</td> </tr> <tr> <td>Approval 1</td> <td>UL listed</td> </tr> <tr> <td>Approval 2</td> <td>Ecolab</td> </tr> </table>	Connector Design	Cable Connector	Connector locking system	screw	Termination	crimp, overmoulded on cable	Wire gauge (mm)	0,25	Wire gauge (AWG)	24	Upper temperature	105 °C	Lower temperature	-40 °C	material housing	PVC	Insulation single lead	PVC	Single lead structure	32 x 0,1	Cable sheath Ø	6	Conductor resistance	<79 Ω/Km (20°C)	Temperature range cable movable °C from	-5	Temperature range cable movable °C to	105	Temperature range cable fixed °C from	-40	Temperature range cable fixed °C to	105	Bending radius cable fixed	min. 5 x D	Bending radius cable movable	min. 10 x D	Approval 1	UL listed	Approval 2	Ecolab	<h3 style="color: #0070C0;">Electrical parameters</h3> <table border="0"> <tr> <td>Rated voltage</td> <td>30 V</td> </tr> <tr> <td>Rated impulse voltage</td> <td>800 V</td> </tr> <tr> <td>Pollution degree</td> <td>3</td> </tr> <tr> <td>Overvoltage category</td> <td>II</td> </tr> <tr> <td>Material group</td> <td>II</td> </tr> <tr> <td>Rated current (40°C)</td> <td>2 A</td> </tr> <tr> <td>Volume resistivity</td> <td>≤ 3 mΩ</td> </tr> <tr> <td>EMV compliance</td> <td>not shielded</td> </tr> <tr> <td>Degree of protection</td> <td>IP69K</td> </tr> <tr> <td>Mechanical operation</td> <td>> 100 Mating cycles</td> </tr> </table> <h3 style="color: #0070C0;">Material</h3> <table border="0"> <tr> <td>Material of contact</td> <td>CuSn (Bronze)</td> </tr> <tr> <td>Contact plating</td> <td>Au (gold)</td> </tr> <tr> <td>Material of contact body</td> <td>PP</td> </tr> <tr> <td>Material of housing</td> <td>PP</td> </tr> </table>	Rated voltage	30 V	Rated impulse voltage	800 V	Pollution degree	3	Overvoltage category	II	Material group	II	Rated current (40°C)	2 A	Volume resistivity	≤ 3 mΩ	EMV compliance	not shielded	Degree of protection	IP69K	Mechanical operation	> 100 Mating cycles	Material of contact	CuSn (Bronze)	Contact plating	Au (gold)	Material of contact body	PP	Material of housing	PP
Connector Design	Cable Connector																																																																				
Connector locking system	screw																																																																				
Termination	crimp, overmoulded on cable																																																																				
Wire gauge (mm)	0,25																																																																				
Wire gauge (AWG)	24																																																																				
Upper temperature	105 °C																																																																				
Lower temperature	-40 °C																																																																				
material housing	PVC																																																																				
Insulation single lead	PVC																																																																				
Single lead structure	32 x 0,1																																																																				
Cable sheath Ø	6																																																																				
Conductor resistance	<79 Ω/Km (20°C)																																																																				
Temperature range cable movable °C from	-5																																																																				
Temperature range cable movable °C to	105																																																																				
Temperature range cable fixed °C from	-40																																																																				
Temperature range cable fixed °C to	105																																																																				
Bending radius cable fixed	min. 5 x D																																																																				
Bending radius cable movable	min. 10 x D																																																																				
Approval 1	UL listed																																																																				
Approval 2	Ecolab																																																																				
Rated voltage	30 V																																																																				
Rated impulse voltage	800 V																																																																				
Pollution degree	3																																																																				
Overvoltage category	II																																																																				
Material group	II																																																																				
Rated current (40°C)	2 A																																																																				
Volume resistivity	≤ 3 mΩ																																																																				
EMV compliance	not shielded																																																																				
Degree of protection	IP69K																																																																				
Mechanical operation	> 100 Mating cycles																																																																				
Material of contact	CuSn (Bronze)																																																																				
Contact plating	Au (gold)																																																																				
Material of contact body	PP																																																																				
Material of housing	PP																																																																				