

Product sheet

Miniature connector



Product
Pole

Contacts: 12, male panel mount connector
12


Area
Article number

Bayonet IP40 Series 678
99 0651 00 12


Illustration



Scale drawing



Contact Arrangement



| | X | Y |
|---|-------|-------|
| A | 0,41 | -3,45 |
| B | -2,29 | -3,61 |
| C | -4,10 | -1,21 |
| D | -3,20 | 1,34 |
| E | -2,71 | 3,59 |
| F | -0,41 | 3,45 |
| G | 2,29 | 3,61 |
| H | 4,10 | 1,21 |
| J | 3,20 | -1,34 |
| K | 2,71 | -3,59 |
| L | -2,00 | -1,51 |
| M | 2,00 | 1,51 |

You can find the assembly instruction on the next page.

Technical data

Common values

| | |
|--------------------------|----------------------------|
| Connector Design | Male panel mount connector |
| Connector locking system | Bayonet |
| Termination | Solder |
| Wire gauge (mm) | 0.25 mm ² |
| Wire gauge (AWG) | 24 |
| Cable outlet | - |
| Upper temperature | 85 °C |
| Lower temperature | -40 °C |

Electrical values

| | |
|-----------------------|---------------------|
| Rated voltage | 60 V |
| Rated impulse voltage | 500 V |
| Pollution degree | 1 |
| Overvoltage category | I |
| Material group | III |
| Rated current (40°C) | 3 A |
| Volume resistivity | ≤ 3 mΩ |
| EMV compliance | not shielded |
| Degree of protection | IP40 |
| Mechanical operation | > 500 mating cycles |

Material

| | |
|--------------------------|-----------------|
| Material of contact | CuZn (Brass) |
| Contact plating | Au (Gold) |
| Material of contact body | PBT (UL 94 V-0) |
| Material of housing | PA (UL 94 V-0) |

Contacts: 12, male panel mount connector

Product
Pole

Contacts: 12, male panel mount connector
12

Area
Article number

Bayonet IP40 Series 678
99 0651 00 12

Installation instructions / Mounting cutout

