

# Product sheet

## Subminiature connector



Product	<b>Contacts 4, Female cable connector IP 67, shielded</b>	Area	<b>Push-Pull IP67 Series 430</b>
Pole	<b>4</b>	Article number	<b>99 4910 00 04</b>

Illustration	Scale drawing	Contact Arrangement															
		<table border="1" style="margin-left: 20px;"> <thead> <tr> <th></th> <th>X</th> <th>Y</th> </tr> </thead> <tbody> <tr> <td>1</td> <td>-1,11</td> <td>-1,11</td> </tr> <tr> <td>2</td> <td>-1,11</td> <td>1,11</td> </tr> <tr> <td>3</td> <td>1,11</td> <td>1,11</td> </tr> <tr> <td>4</td> <td>1,11</td> <td>-1,11</td> </tr> </tbody> </table>		X	Y	1	-1,11	-1,11	2	-1,11	1,11	3	1,11	1,11	4	1,11	-1,11
	X	Y															
1	-1,11	-1,11															
2	-1,11	1,11															
3	1,11	1,11															
4	1,11	-1,11															

You can find the item description on the next page.

## Technical data

### Common values

Connector Design	Female cable connector
Connector locking system	Push-Pull
Termination	Solder
Wire gauge (mm)	0.25 mm <sup>2</sup>
Wire gauge (AWG)	24
Cable outlet	3.5 - 5 mm
Upper temperature	85 °C
Lower temperature	-40 °C

### Cable data

material housing	-
Insulation single lead	-
Single lead structure	-
Conductor resistance	-

### Electrical values

Rated voltage	125 V
Rated impulse voltage	1500 V
Pollution degree	2
Overvoltage category	I
Material group	II
Rated current (40°C)	3 A
Volume resistivity	≤ 5 mΩ
EMV compliance	shieldable
Degree of protection	IP67
Mechanical operation	> 500 mating cycles

### Material

Material of contact	CuSn (Bronze)
Contact plating	Au (Gold)
Material of contact body	PBT, PA
Material of housing	PA

Contacts: 4, Female cable connector IP 67, shielded

# Product sheet

## Subminiature connector



Product	<b>Contacts 4, Female cable connector IP 67, shielded</b>	Area	<b>Push-Pull IP67 Series 430</b>
Pole	<b>4</b>	Article number	<b>99 4910 00 04</b>

### Item description

