

Product sheet

Miniature connector



Product	Contacts: 4, Male panel mount connector, dip-solder, screwed from the front, with UL approval	Area	M16 IP67 Series 423/ 723/ 425
Pole	4	Article number	09 0111 99 04

Illustration

Scale drawing

Contact Arrangement

	X	Y
1	3,32	-1,08
2	2,05	2,83
3	-2,05	2,83
4	-3,32	-1,08

You can find the assembly instruction on the next page.

Technical data

Common values

Connector Design	Male panel mount connector
Connector locking system	screw
Termination	dip-solder
Wire gauge (mm)	-
Wire gauge (AWG)	-
Upper temperature	95 °C
Lower temperature	-40 °C

Electrical values

Rated voltage	250 V
Rated impulse voltage	1500 V
Pollution degree	1
Overvoltage category	I
Material group	III
Rated current (40°C)	6 A
Volume resistivity	≤ 5 mΩ shielded
EMV compliance	IP67
Degree of protection	> 500 mating cycles
Mechanical operation	

Material

Material of contact	CuZn (Brass)
Contact plating	Au (Gold)
Material of contact body	PBT (UL 94 V-0)
Material of housing	Nickel-plated zinc die casting

Contacts: 4, Male panel mount connector, dip-solder, screwed from the front, gold plated contacts, with UL approval



Product sheet
Miniature connector



Product

**Contacts: 4, Male panel mount connector,
dip-solder, screwed from the front, with
UL approval**

Area
Article number

**M16 IP67 Series 423/ 723/ 425
09 0111 99 04**

Pole

4

Installation instructions / Mounting cutout

