

Product description	M8 cable connector, Contacts: 3, not shielded, moulded on cable, IP67, UL listed, PUR black, 3 x 0.34 mm²
Area	M8 series 718
Order number	77 3405 0000 50003-0200

Illustration	Scale drawing	Contact arrangement

Technical data

General values

<p>Notice</p> <p>Connector design</p> <p>Connector locking system</p> <p>Termination</p> <p>Wire gauge (mm)</p> <p>Wire gauge (AWG)</p> <p>Upper limit temperature</p> <p>Lower limit temperature</p> <p>Customs tariff number</p>	<p>Please note that, due to the change from the old to the new order number, there may be deviations in the technical specifications. For questions about product details, please use the 'Contact Customer Service' form on the right.</p> <p>cable connector</p> <p>screw</p> <p>moulded on cable</p> <p>0.34 mm²</p> <p>22</p> <p>85 °C</p> <p>- 25 °C</p> <p>85444290</p>
--	--

Electrical values

<p>Rated current (40 °C)</p> <p>Rated voltage</p> <p>Rated impulse voltage</p> <p>Pollution degree</p> <p>Overvoltage category</p> <p>Insulating material group</p> <p>EMC compliance</p> <p>Degree of protection</p> <p>Mechanical operation</p>	<p>4 A</p> <p>60 V</p> <p>1500 V</p> <p>3</p> <p>II</p> <p>II</p> <p>not shielded</p> <p>IP67</p> <p>> 100 Mating cycles</p>
---	---

Material

<p>Contact material</p> <p>Contact plating</p> <p>Contact body material</p> <p>Housing material</p>	<p>CuZn (brass)</p> <p>Au (gold)</p> <p>PUR</p> <p>PUR</p>
---	--

Cable data

<p>Cable length</p> <p>Sheath material</p> <p>Single-lead insulation</p> <p>Single-lead structure</p> <p>Cable diameter</p> <p>Conductor resistance</p> <p>Temperature range, moving cable, °C from</p> <p>Temperature range, moving cable, °C to</p> <p>Temperature range, fixed cable, °C from</p> <p>Temperature range, fixed cable, °C to</p> <p>Bending radius, fixed cable</p> <p>Bending radius, moving cable</p> <p>Approval 1</p> <p>UL style 1</p>	<p>2 m</p> <p>PUR</p> <p>PP</p> <p>42 x 0,1 mm</p> <p>4.3 mm</p> <p>60Ω/Km</p> <p>- 25 °C</p> <p>90 °C</p> <p>-50 °C</p> <p>90 °C</p> <p>≥ 5 x Ø</p> <p>≥ 10 x Ø</p> <p>UL listed</p> <p>AWM20549</p>
--	---

Product description	M8 cable connector, Contacts: 3, not shielded, moulded on cable, IP67, UL listed, PUR black, 3 x 0.34 mm²
Area	M8 series 718
Order number	77 3405 0000 50003-0200

Security notices

The connectors are designed for use in plant, control system and electrical equipment. The end user is responsible for checking whether the connectors are suitable for use in other applications.

Connectors with degree of protection IP 67 and IP 68 are not suitable for use under water. When used outdoors, the connectors must be separately protected against corrosion. For further information about IP degrees of protection refer to 'Technical support' in the Download Centre.

To lock the cable connector to the equipment connector, the threaded ring is tightened until it is 'finger-tight' (approx. 50 cNm).