


Product **Contacts: 4, Male panel mount connector with single wires**

Area **M16 IP67 Series 423/ 723/ 425**
Article number **09 0111 702 04**

Illustration



Contact Arrangement



	X	Y
1	3,32	-1,08
2	2,05	2,83
3	-2,05	2,83
4	-3,32	-1,08

You can find the assembly instruction on the next page.

Technical data

General features

Connector Design	male panel mount connector
Connector locking system	bolted
Termination	Strands
Wire gauge (mm)	0,75 mm ²
Wire gauge (AWG)	22
Upper temperature	95 °C
Lower temperature	-40 °C

Cable data

Approval 1	UL
------------	----

Electrical parameters

Rated voltage	300 V
Rated impulse voltage	1500 V
Pollution degree	1
Overvoltage category	I
Material group	II
Rated current (40°C)	5 A
Volume resistivity	≤ 5 mΩ
EMV compliance	shielded
Degree of protection	IP67
Mechanical operation	> 500 Mating cycles

Material

Material of contact	CuSn (Bronze)
Contact plating	Ag (silver)
Material of contact body	PBT (UL 94 V-0)

Product **Contacts: 4, Male panel mount connector with single wires**

Area **M16 IP67 Series 423/ 723/ 425**
Article number **09 0111 702 04**

Installation instructions / Mounting cutout

