

Product sheet

Subminiature connector



Product	Contacts: 3, cable plug connector, injection-moulded cable	Area	Snap-in IP67 Series 620
Pole	3	Article number	79 9237 020 03

Illustration	Scale drawing	Contact Arrangement
		<ul style="list-style-type: none"> 1 braun/brown 2 blau/blue 3 schwarz/black

You can find the item description on the next page.

Technical data

Common values

Connector Design	Cable plug connector
Connector locking system	Snap
Termination	injection-moulded cable
Wire gauge (mm)	0.25 mm ²
Wire gauge (AWG)	24
Cable outlet	-
Upper temperature	70 °C
Lower temperature	-40 °C

Cable data

material housing	PVC
Insulation single lead	PVC
Single lead structure	32 x 0.1 mm
Cable sheath Ø	4.5
Conductor resistance	72Ω/Km (20°C)
Temperature range cable movable c from	-5
Temperature range cable movable c to	70
Temperature range cable fixed c from	-40
Temperature range cable fixed c to	70
Bending radius cable fixed	22 mm
Bending radius cable movable	45 mm
Approval	-

Electrical values

Rated voltage	125 V
Rated impulse voltage	1500 V
Pollution degree	2
Overvoltage category	II
Material group	II
Rated current (40°C)	3 A
Volume resistivity	≤ 3 mΩ
EMV compliance	not shieldable
Degree of protection	IP67
Mechanical operation	> 500 mating cycles

Material

Material of contact	CuZn (Brass)
Contact plating	Au (Gold)
Material of contact body	PA (UL 94 V-0)
Material of housing	PUR

Contacts: 3, cable plug connector, injection-moulded cable

Product sheet
Subminiature connector

Product
Pole

**Contacts: 3, cable plug connector,
injection-moulded cable**
3

Area
Article number

Snap-in IP67 Series 620
79 9237 020 03

Item description

