

enclosures:  
size "21.21" page:

**insulating type** ..... 526 - 527  
(CK IN, CKG/MKG VN/VAN \*)

**metallic type**  
(CKAX I, CKAX/MKAX IAP/AP/VG) 223 and 528  
(CKAG/MKAG V/VA \*) ..... 529

**IP68** ..... 416 - 418  
(CGK I, CGK/MGK IAP, CGK/MGK V)

\*) angled enclosures cannot be used with CX 8 J6IM

refer to catalogue page CN.16

**USB female - female connectors**



**NEW**

**patch cable USB**



description	part No.	part No.
-------------	----------	----------

- female insert with USB 2.0 female - female connector	<b>CUK 2FT</b>	
- female insert with USB 3.0 female - female connector	<b>CUK 3FT</b>	

patch cable USB-A / USB-A, 2 m **	dimensions in mm	part No.
-----------------------------------	------------------	----------


** 5 m on request		
-------------------	--	--

**USB connector features:**


- USB-A / USB-A Hi-Speed - 2.0 or 3.0 insert
- temperature range: from -25 °C to +80 °C

dimensions in mm

**CUK 2FT**







**CUK 3FT**



**CW 2 UAM**

dimensions in mm

**CW UAM**



dimensions shown are not binding and may be changed without notice