

Product sheet

Subminiature connector




Product	Contacts: 4, Cable plug connector with strain relief	Area	Snap-in IP40 Series 719
Pole	4	Article number	09 9767 70 04

Illustration



Scale drawing



Contact Arrangement

	X	Y
1	1,06	-1,06
2	1,06	1,06
3	-1,06	1,06
4	-1,06	-1,06

You can find the item description on the next page.

Technical data

Common values

Connector Design	Cable plug connector
Connector locking system	Snap
Termination	Solder
Wire gauge (mm)	0.25 mm ²
Wire gauge (AWG)	24
Cable outlet	max. 4 mm
Upper temperature	70 °C
Lower temperature	-25 °C

Electrical values

Rated voltage	60 V
Rated impulse voltage	800 V
Pollution degree	1
Overvoltage category	II
Material group	III
Rated current (40°C)	3 A
Volume resistivity	≤ 3 mΩ
EMV compliance	not shieldable
Degree of protection	IP40
Mechanical operation	> 100 mating cycles

Cable data

material housing	-
Insulation single lead	-
Single lead structure	-
Conductor resistance	-

Material

Material of contact	CuZn (Brass)
Contact plating	Au (Gold)
Material of contact body	PA
Material of housing	PA

Contacts: 4, Cable plug connector with strain relief, max. cable outlet 4 mm

Product

Contacts: 4, Cable plug connector with strain relief
4

Area
Article number

Snap-in IP40 Series 719
09 9767 70 04

Pole

Item description

